

View Online at <https://aerobasegroup.com/nsn/5950-01-176-4966>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.312 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.688 inches single mounting facility single center group

Mounting Hole Diameter:

0.188 inches single group

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Maximum Transformer Power Rating:

375.0 volt-ampere single component

Winding Shielding Method:

Internal shield grounded to core single component

Body Length:

4.250 inches

Body Width:

3.625 inches

Body Height:

5.500 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Features Provided:

Color coded terminal

Winding Operating Current:

7.0 amperes ac single component single secondary

Winding Operating Voltage:

52.00 ac volts single component single secondary

Terminal Type And Quantity:

9 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0