

View Online at <https://aerobasegroup.com/nsn/5950-01-176-5616>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.740 inches single mounting facility single center group and 2.760 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.240 inches single mounting facility single center group and 2.260 inches single mounting facility single center group

Overall Height:

2.659 inches

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Three phase to single phase single component and three phase to three phase single component

Transformer Winding Connection Type:

Delta-delta

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Length:

4.060 inches

Body Width:

3.320 inches

Body Height:

2.440 inches

Maximum Operating Temp:

155.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 8 secondary single component

Thread Size:

0.190 inches single group

Winding Operating Current:

300.0 milliamperes dc single component 4th secondary

Winding Power Rating:

39.8 volts-amperes single component 3rd secondary

Winding Operating Voltage:

25.00 dc volts single component 4th secondary

Special Features:

One primary winding; eight secondary windings

Thread Series Designator:

Unf single group

Terminal Type And Quantity:

26 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0