## NSN 5950-01-178-4306

Reactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-178-4306

Deliability Indicators
Reliability Indicator:
Not established
Turn Quantity:
28 single component single winding
Mounting Hole Diameter:
0.093 inches single group
Inductance Type:
Fixed
Inductance Rating:
52.00 microhenries single component single winding
Frequency Rating:
2.0 kilohertz single component
Body Length:
0.750 inches
Body Width:
0.550 inches
Body Height:
0.325 inches
Maximum Operating Temp:
100.0 degrees celsius
Distance Between Mounting Facility Centers:
0.590 inches single mounting facility single center group
Winding Quantity:
1 single component
Inclosure Type:
Fully enclosed
Mounting Facility Quantity:
2 single group
Mounting Method:
Unthreaded hole single group
Rating Method:
Electrical single component single winding and winding turns single component single winding
Winding Conductor Size:
0.01264 inches american wire gage single component single winding
Winding Operating Current:
330.0 milliamperes dc single component single winding
Dc Resistance Rating In Ohms:
0.150 single component single winding
Terminal Type And Quantity:
2 wire lead
Shelf Life:
N/a

## NSN 5950-01-178-4306

Reactor - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A058b0