

View Online at <https://aerobasegroup.com/nsn/5950-01-179-4820>

Reliability Indicator:

Not established

Overall Length:

Between 4.970 inches and 5.030 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

4.360 inches single mounting facility all center groupings and 4.390 inches single mounting facility all center groupings

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.735 inches single mounting facili type 2nd center group and 3.765 inches single mounting facili type 2nd center group

Overall Height:

Between 5.600 inches and 5.660 inches

Overall Width:

Between 4.470 inches and 4.530 inches

Frequency Rating:

47.0 hertz single component and 440.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Core grounded single component

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 all groupings

Mounting Method:

Threaded hole all groupings

Winding Function And Quantity:

1 primary single component and 5 secondary single component

Features Provided:

W/rectifier

Thread Size:

0.190 inches all groupings

Winding Operating Current:

6.3 amperes dc single component 2nd secondary

Winding Power Rating:

88.0 volts-amperes single component 3rd secondary

Winding Operating Voltage:

5.00 dc volts single component 1st secondary

Special Features:

1 primary winding; 5 secondary windings

Thread Series Designator:

Unf all groupings

Terminal Type And Quantity:

15 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0