

View Online at <https://aerobasegroup.com/nsn/5950-01-181-1653>

Reliability Indicator:

Not established

Hazardous Locations/environmental Protection:

Vibration resistant and moisture resistant

Overall Length:

0.900 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.690 inches single mounting facility single center group and 0.710 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.365 inches single mounting facility single center group and 0.385 inches single mounting facility single center group

Overall Width:

0.875 inches

Frequency Rating:

380.0 hertz single component and 420.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Height:

0.531 inches

Maximum Operating Temp:

105.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Method:

Terminal single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Current:

3.0 milliamperes ac single component single secondary

Winding Power Rating:

0.03 volts-amperes single component single secondary

Winding Operating Voltage:

9.985 ac volts single component single secondary and 10.15 ac volts single component single secondary

Terminal Type And Quantity:

5 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0