## NSN 5950-01-182-3351

Reactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-182-3351

Reliab	ility	Indic	ator:
--------	-------	-------	-------

Not established

**Hazardous Locations/environmental Protection:** 

Vibration resistant

**Overall Length:** 

Between 0.720 inches and 0.906 inches

**Mounting Hole Diameter:** 

0.146 inches single group and 0.166 inches single group

**Inductance Type:** 

Fixed

**Inductance Rating:** 

8.00 microhenries single component all winding

Frequency Rating:

10.0 kilohertz single component

**Overall Diameter:** 

Between 0.845 inches and 0.905 inches

**Maximum Operating Temp:** 

130.0 degrees celsius

**Winding Quantity:** 

2 single component

**Inclosure Type:** 

Fully enclosed

**Mounting Facility Quantity:** 

1 single group

**Mounting Method:** 

Unthreaded hole single group

**Rating Method:** 

Electrical single component single winding

**Winding Operating Current:** 

15.0 amperes dc single component single winding

Dc Resistance Rating In Ohms:

0.005 single component all winding

**Test Data Document:** 

81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Terminal Type And Quantity:**

4 pin

**Specification Data:** 

81349-mil-t-27/287 government specification

Shelf Life:

N/a

**Unit Of Measure:** 

--

## NSN 5950-01-182-3351

Reactor - Page 2 of 2



em			

No

Fiig:

A058b0