NSN 5950-01-185-2910

Radio Frequency Coil - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-185-2910

Reliability Indicator: Not established Hazardous Locations/environmental Protection: Moisture resistant Inductance Rating: 10.00 microhenries single component single winding Coil Form Type: Solid single component Core Construction: Powdered single component Body Length: Between 0.260 inches and 0.280 inches Body Width: Between 0.140 inches and 0.160 inches Body Height: Between 0.270 inches and 0.300 inches Maximum Operating Temp: 125.0 degrees celsius Inclosure Type: Fully enclosed Mounting Method: Terminal single group Rating Method: Tinned wire leads Winding Conductor Size: 0.02535 inches american wire gage single component single winding Durating Method: 1.100 single component single winding Charlestance Rating In Ohms: 1.100 single component single winding Durating Factor: 1.100 single component single winding Charlestance Rating In Ohms: 1.100 single component single winding<	
Hazardous Locations/environmental Protection: Moisture resistant Inductance Rating: 10.00 microhenries single component single winding Coil Form Type: Solid single component Core Construction: Powdered single component Between 0.260 inches and 0.280 inches Body Length: Between 0.140 inches and 0.160 inches Body Height: Between 0.270 inches and 0.300 inches Maximum Operating Temp: 125.0 degrees celsius Inclosure Type: Fully enclosed Mounting Method: Terminal single group Rating Method: Tinned wire leads Winding Conductor Size: 0.02535 inches american wire gage single component single winding De Resistance Rating In Ohms: 1.100 single component single winding Der Resistance Rating In Ohms: 1.100 single component single winding Duality Factor: 75 single component single winding Terminal Type And Quantity: 2 pin Shelf Life: N/a Unt Of Measure: I pin </td <td>Reliability Indicator:</td>	Reliability Indicator:
Moisture resistant Inductance Rating: 10.00 microhenries single component single winding Coil Form Type: Solid single component Core Construction: Powdered single component Body Length: Between 0.260 inches and 0.280 inches Body Width: Between 0.140 inches and 0.160 inches Body Height: Between 0.270 inches and 0.300 inches Maximum Operating Temp: 125.0 degrees celsius Inclosure Type: Fully enclosed Mounting Method: Terminal single group Rating Method: Electrical single component single winding Features Provided: Tinned wire leads Winding Conductor Size: 0.02535 inches american wire gage single component single winding Dc Resistance Rating In Ohms: 1.100 single component single winding Co	Not established
Inductance Rating: 10.00 microhenries single component single winding Coil Form Type: Solid single component Core Construction: Powdered single component Body Length: Between 0.260 inches and 0.280 inches Body Width: Between 0.260 inches and 0.160 inches Body Height: Between 0.270 inches and 0.300 inches Maximum Operating Temp: 125.0 degrees celsius Inclosure Type: Fully enclosed Mounting Method: Terminal single group Rating Method: Electrical single component single winding Features Provided: Tinned wire leads Winding Conductor Size: 0.02535 inches american wire gage single component single winding Winding Operating Current: 55.00 milliamperes dc single component single winding Dire Resistance Rating In Ohms: 1.100 single component single winding Cuality Factor: 75 single component single winding Terminal Type And Quantity: 2 pin Shefl Liffe: N/a Unit Of Measure: - - Demilitarization:	Hazardous Locations/environmental Protection:
10.00 microhenries single component single windingCoil Form Type:Solid single componentCore Construction:Powdered single componentBody Length:Between 0.260 inches and 0.280 inchesBody Width:Between 0.140 inches and 0.160 inchesBody Height:Between 0.270 inches and 0.300 inchesMaximum Operating Temp:125.0 degrees celsiusInclosure Type:Fully enclosedMounting Method:Terminal single groupRating Method:Tinned wire leadsWinding Conductor Size:0.02535 inches american wire gage single component single windingVinding Operating Current:55.0.0 milliamperes dc single component single windingCuality Factor:75 single component single windingCuality Factor:74N/aUnt of Measure:TimeN/aCuality Factor:N/aCuality Factor:Torminal Type And Quantity:2 pinShelf Life:N/aUnit of Measure:Torminal Type And Quantity:2	Moisture resistant
Coil Form Type:Solid single componentCore Construction:Powdered single componentBody Length:Between 0.260 inches and 0.280 inchesBody Width:Between 0.140 inches and 0.160 inchesBody Height:Between 0.270 inches and 0.300 inchesMaximum Operating Temp:125.0 degrees celsiusInclosure Type:Fully enclosedMounting Method:Terminal single groupRating Method:Electrical single component single windingFeatures Provided:Tinned wire leadsWinding Conductor Size:0.02535 inches american wire gage single component single windingPresistance Rating In Ohms:1.100 single component single windingCuality Factor:75 single component single windingCuality Factor:74MaUnit Of Measure:ToFactor:Factor:Factor:Factor:Factor:Factor:Factor:Factor:Factor:Factor:Factor:Factor:Factor:Factor:Factor:Factor:Factor:Factor:Factor:	Inductance Rating:
Solid single component Core Construction: Powdered single component Body Length: Between 0.260 inches and 0.280 inches Body Width: Between 0.140 inches and 0.160 inches Body Height: Between 0.270 inches and 0.300 inches Maximum Operating Temp: 125.0 degrees celsius Inclosure Type: Fully enclosed Mounting Method: Terminal single group Rating Method: Electrical single component single winding Features Provided: Tinned wire leads Vinding Conductor Size: 0.02535 inches american wire gage single component single winding Derasistance Rating In Ohms: 1.100 single component single winding Curent: 1.100 single component single winding Curent: 1.100 single component single winding Cuality Factor: 2 pin Shelf Life: N/a Unit of Measure:	10.00 microhenries single component single winding
Core Construction: Powdered single component Body Length: Between 0.260 inches and 0.280 inches Body Width: Between 0.140 inches and 0.160 inches Body Height: Between 0.270 inches and 0.300 inches Maximum Operating Temp: 125.0 degrees celsius Inclosure Type: Fully enclosed Mounting Method: Terminal single group Rating Method: Electrical single component single winding Features Provided: Tinned wire leads Winding Conductor Size: 0.02535 inches american wire gage single component single winding Winding Operating Current: 550.0 milliamperes dc single component single winding De Resistance Rating In Ohms: 1.100 single component single winding Guality Factor: 75 single component single winding Terminal Type And Quantity: 2 pin Shelf Life: N/a Unit of Measure: Demilitarization:	Coil Form Type:
Powdered single component Body Length: Between 0.260 inches and 0.280 inches Body Width: Between 0.140 inches and 0.160 inches Body Height: Between 0.270 inches and 0.300 inches Maximum Operating Temp: 125.0 degrees celsius Inclosure Type: Fully enclosed Mounting Method: Terminal single group Rating Method: Electrical single component single winding Features Provided: Tinned wire leads Winding Conductor Size: 0.02535 inches american wire gage single component single winding Winding Operating Current: 550.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 1.100 single component single winding Cuality Factor: 75 single component single winding Terminal Type And Quantity: 2 pin Shelf Life: N/a Unit Of Measure: 	Solid single component
Body Length: Between 0.260 inches and 0.280 inches Body Width: Between 0.140 inches and 0.160 inches Body Height: Between 0.270 inches and 0.300 inches Maximum Operating Temp: 125.0 degrees celsius Inclosure Type: Fully enclosed Mounting Method: Terminal single group Rating Method: Electrical single component single winding Features Provided: Tinned wire leads Winding Conductor Size: 0.02535 inches american wire gage single component single winding Vinding Operating Current: 550.0 milliamperes dc single component single winding Quality Factor: 75 single component single winding Quality Factor: 75 single component single winding Terminal Type And Quantity: 2 pin Shelf Life: N/a Unit Of Measure: - Demilitarization:	Core Construction:
Between 0.260 inches and 0.280 inches Body Width: Between 0.140 inches and 0.160 inches Body Height: Between 0.270 inches and 0.300 inches Maximum Operating Temp: 125.0 degrees celsius Inclosure Type: Fully enclosed Mounting Method: Terminal single group Rating Method: Electrical single component single winding Features Provided: Tinned wire leads Winding Operating Current: 550.0 milliamperes dc single component single winding Do Resistance Rating In Ohms: 1.100 single component single winding Cuality Factor: 75 single component single winding Terminal Type And Quantity: 2 pin Shelf Life: N/a Unit Of Measure: Demilitarization:	Powdered single component
Body Width: Between 0.140 inches and 0.160 inches Body Height: Between 0.270 inches and 0.300 inches Maximum Operating Temp: 125.0 degrees celsius Inclosure Type: Fully enclosed Mounting Method: Terminal single group Rating Method: Electrical single component single winding Features Provided: Tinned wire leads Winding Conductor Size: 0.02535 inches american wire gage single component single winding Winding Operating Current: 550.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 1.100 single component single winding Terminal Type And Quantity: 2 pin Shelf Life: N/a Unit Of Measure: 	Body Length:
Between 0.140 inches and 0.160 inches Body Height: Between 0.270 inches and 0.300 inches Maximum Operating Temp: 125.0 degrees celsius Inclosure Type: Fully enclosed Mounting Method: Terminal single group Rating Method: Terminal single component single winding Features Provided: Tinned wire leads Winding Conductor Size: 0.02535 inches american wire gage single component single winding Derasistance Rating In Ohms: 1.100 single component single winding Derasistance Rating In Ohms: 1.100 single component single winding Terminal Type And Quantity: 2 pin Shelf Life: N/a Unit Of Measure: - Demilitarization:	Between 0.260 inches and 0.280 inches
Body Height: Between 0.270 inches and 0.300 inches Maximum Operating Temp: 125.0 degrees celsius Inclosure Type: Fully enclosed Mounting Method: Terminal single group Rating Method: Electrical single component single winding Features Provided: Tinned wire leads Winding Conductor Size: 0.02535 inches american wire gage single component single winding Winding Operating Current: 550.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 1.100 single component single winding Cuality Factor: 75 single component single winding Terminal Type And Quantity: 2 pin Shelf Life: N/a Unit Of Measure: 	Body Width:
Between 0.270 inches and 0.300 inches Maximum Operating Temp: 125.0 degrees celsius Inclosure Type: Fully enclosed Mounting Method: Terminal single group Rating Method: Electrical single component single winding Features Provided: Tinned wire leads Winding Conductor Size: 0.02535 inches american wire gage single component single winding Winding Operating Current: 550.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 1.100 single component single winding Guality Factor: 75 single component single winding Terminal Type And Quantity: 2 pin Shelf Life: N/a Unit Of Measure: 	Between 0.140 inches and 0.160 inches
Maximum Operating Temp: 125.0 degrees celsius Inclosure Type: Fully enclosed Mounting Method: Terminal single group Rating Method: Electrical single component single winding Features Provided: Tinned wire leads Winding Conductor Size: 0.02535 inches american wire gage single component single winding Winding Operating Current: 550.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 1.100 single component single winding Cuality Factor: 75 single component single winding Terminal Type And Quantity: 2 pin Shelf Life: N/a Unit Of Measure: Demilitarization:	Body Height:
125.0 degrees celsius Inclosure Type: Fully enclosed Mounting Method: Terminal single group Rating Method: Electrical single component single winding Features Provided: Tinned wire leads Winding Conductor Size: 0.02535 inches american wire gage single component single winding Winding Operating Current: 550.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 1.100 single component single winding Quality Factor: 75 single component single winding Terminal Type And Quantity: 2 pin Shelf Life: N/a Unit Of Measure:	Between 0.270 inches and 0.300 inches
Inclosure Type: Fully enclosed Mounting Method: Terminal single group Rating Method: Electrical single component single winding Features Provided: Tinned wire leads Winding Conductor Size: 0.02535 inches american wire gage single component single winding Ouz535 inches american wire gage single component single winding Vinding Operating Current: 550.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 1.100 single component single winding Quality Factor: 75 single component single winding Terminal Type And Quantity: 2 pin Shelf Life: N/a Unit Of Measure: Demilitarization:	Maximum Operating Temp:
Fully enclosed Mounting Method: Terminal single group Rating Method: Electrical single component single winding Features Provided: Tinned wire leads Winding Conductor Size: 0.02535 inches american wire gage single component single winding Winding Operating Current: 550.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 1.100 single component single winding Muality Factor: 75 single component single winding Terminal Type And Quantity: 2 pin Shelf Life: N/a Unit Of Measure: 	125.0 degrees celsius
Mounting Method: Terminal single group Rating Method: Electrical single component single winding Features Provided: Tinned wire leads Winding Conductor Size: 0.02535 inches american wire gage single component single winding Ouz535 inches american wire gage single component single winding Winding Operating Current: 550.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 1.100 single component single winding Quality Factor: 75 single component single winding Terminal Type And Quantity: 2 pin Shelf Life: N/a Unit Of Measure: 	Inclosure Type:
Terminal single group Rating Method: Electrical single component single winding Features Provided: Tinned wire leads Winding Conductor Size: 0.02535 inches american wire gage single component single winding Winding Operating Current: 550.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 1.100 single component single winding Quality Factor: 75 single component single winding Terminal Type And Quantity: 2 pin Shelf Life: N/a Unit Of Measure: Demilitarization:	Fully enclosed
Rating Method:Electrical single component single windingFeatures Provided:Tinned wire leadsWinding Conductor Size:0.02535 inches american wire gage single component single windingWinding Operating Current:550.0 milliamperes dc single component single windingDc Resistance Rating In Ohms:1.100 single component single windingQuality Factor:75 single component single windingTerminal Type And Quantity:2 pinShelf Life:N/aUnit Of Measure:Demilitarization:	Mounting Method:
Electrical single component single winding Features Provided: Tinned wire leads Winding Conductor Size: 0.02535 inches american wire gage single component single winding Operating Current: 550.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 1.100 single component single winding Quality Factor: 75 single component single winding Terminal Type And Quantity: 2 pin Shelf Life: N/a Unit Of Measure: Demilitarization:	Terminal single group
Features Provided: Tinned wire leads Winding Conductor Size: 0.02535 inches american wire gage single component single winding Winding Operating Current: 550.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 1.100 single component single winding Quality Factor: 75 single component single winding Terminal Type And Quantity: 2 pin Shelf Life: N/a Unit Of Measure: Demilitarization:	Rating Method:
Tinned wire leads Winding Conductor Size: 0.02535 inches american wire gage single component single winding Winding Operating Current: 550.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 1.100 single component single winding Quality Factor: 75 single component single winding Terminal Type And Quantity: 2 pin Shelf Life: N/a Unit Of Measure: Demilitarization:	Electrical single component single winding
Winding Conductor Size: 0.02535 inches american wire gage single component single winding Winding Operating Current: 550.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 1.100 single component single winding Quality Factor: 75 single component single winding Terminal Type And Quantity: 2 pin Shelf Life: N/a Unit Of Measure: Demilitarization:	Features Provided:
0.02535 inches american wire gage single component single winding Winding Operating Current: 550.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 1.100 single component single winding Quality Factor: 75 single component single winding Terminal Type And Quantity: 2 pin Shelf Life: N/a Unit Of Measure: Demilitarization:	Tinned wire leads
Winding Operating Current: 550.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 1.100 single component single winding Quality Factor: 75 single component single winding Terminal Type And Quantity: 2 pin Shelf Life: N/a Unit Of Measure: Demilitarization:	Winding Conductor Size:
550.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 1.100 single component single winding Quality Factor: 75 single component single winding Terminal Type And Quantity: 2 pin Shelf Life: N/a Unit Of Measure: Demilitarization:	0.02535 inches american wire gage single component single winding
Dc Resistance Rating In Ohms: 1.100 single component single winding Quality Factor: 75 single component single winding Terminal Type And Quantity: 2 pin Shelf Life: N/a Unit Of Measure: Demilitarization:	Winding Operating Current:
1.100 single component single winding Quality Factor: 75 single component single winding Terminal Type And Quantity: 2 pin Shelf Life: N/a Unit Of Measure: Demilitarization:	550.0 milliamperes dc single component single winding
Quality Factor: 75 single component single winding Terminal Type And Quantity: 2 pin Shelf Life: N/a Unit Of Measure: Demilitarization:	Dc Resistance Rating In Ohms:
75 single component single winding Terminal Type And Quantity: 2 pin Shelf Life: N/a Unit Of Measure: Demilitarization:	1.100 single component single winding
Terminal Type And Quantity: 2 pin Shelf Life: N/a Unit Of Measure: Demilitarization:	Quality Factor:
2 pin Shelf Life: N/a Unit Of Measure: Demilitarization:	75 single component single winding
2 pin Shelf Life: N/a Unit Of Measure: Demilitarization:	Terminal Type And Quantity:
Shelf Life: N/a Unit Of Measure: Demilitarization:	
Unit Of Measure: Demilitarization:	Shelf Life:
 Demilitarization:	N/a
	Unit Of Measure:
	Demilitarization:
	No

NSN 5950-01-185-2910

Radio Frequency Coil - Page 2 of 2

Fiig: A058b0

