# NSN 5950-01-185-9420

Reactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-185-9420

Reliability	Indicator:
-------------	------------

Not established

#### **Hazardous Locations/environmental Protection:**

Vibration resistant

**Overall Length:** 

Between 0.595 inches and 0.781 inches

#### **Mounting Hole Diameter:**

0.146 inches single group and 0.166 inches single group

**Inductance Type:** 

Fixed

#### **Inductance Rating:**

88.00 microhenries single component 1st winding

#### Frequency Rating:

10.0 kilohertz single component

#### **Overall Diameter:**

Between 0.845 inches and 0.905 inches

#### **Maximum Operating Temp:**

130.0 degrees celsius

# **Winding Quantity:**

2 single component

# **Inclosure Type:**

Fully enclosed

#### **Mounting Facility Quantity:**

1 single group

#### **Mounting Method:**

Unthreaded hole single group

# **Rating Method:**

Electrical single component all winding

# **Winding Operating Current:**

9.0 amperes dc single component 2nd winding

#### Dc Resistance Rating In Ohms:

0.052 single component 1st winding

# **Test Data Document:**

81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

#### **Terminal Type And Quantity:**

4 pin

#### **Specification Data:**

81349-mil-t-27/06 government specification

# Shelf Life:

N/a

#### **Unit Of Measure:**

--

# NSN 5950-01-185-9420

Reactor - Page 2 of 2



_		••	• •				
וו	em	ш	112	rız	211	n	٠.

No

Fiig:

A058b0