

View Online at <https://aerobasegroup.com/nsn/5950-01-186-0212>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

5.200 inches single mounting facility single center group and 5.270 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

5.060 inches single mounting facility single center group and 5.380 inches single mounting facility single center group

Mounting Slot Width:

0.312 inches single group

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

7.500 inches

Body Width:

6.120 inches

Body Height:

6.000 inches

End Application:

Countermeasures systems. Austin ship class lpd-4 amphibious transport docks. Arleigh burke class ddg.

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Flange single group and slot single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Current:

9.0 amperes ac single component single secondary

Criticality Code Justification:

Feat

Winding Operating Voltage:

440.00 ac pounds per hour wet single component single primary

Special Features:

Weapon system essential

Terminal Type And Quantity:

4 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0