# NSN 5950-01-186-6707

Reactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-186-6707

# **Reliability Indicator:**

Not established

#### Center To Center Distance Between Mounting Facilities Parallel To Length:

2.188 inches single mounting facility single center group

# Center To Center Distance Between Mounting Facilities Parallel To Width:

2.016 inches single mounting facility single center group

#### **Mounting Slot Width:**

0.156 inches single group

#### **Inductance Type:**

Fixed

#### **Inductance Rating:**

1.00 henry single component single winding

#### Frequency Rating:

60.0 hertz single component

#### **Body Length:**

2.875 inches

#### **Body Width:**

2.500 inches

#### **Body Height:**

2.531 inches

# **Maximum Operating Temp:**

130.0 degrees celsius

#### Winding Quantity:

1 single component

# **Inclosure Type:**

Fully enclosed

# **Mounting Facility Quantity:**

4 single group

#### **Mounting Method:**

Slot single group

# **Rating Method:**

Electrical single component single winding

# **Winding Operating Current:**

325.0 milliamperes dc single component single winding

# Dc Resistance Rating In Ohms:

44.000 single component single winding

# **Test Data Document:**

81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# **Terminal Type And Quantity:**

2 tab, solder lug

# **Specification Data:**

81349-mil-t-27/179 government specification

# NSN 5950-01-186-6707

Reactor - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A058b0