## NSN 5950-01-188-6340

Reactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-188-6340

| Reliability Indicator:  |
|---|
| Not established   |
| Turn Quantity:  |
| 35 single component single winding  |
| Inductance Type:  |
| Swinging  |
| Inductance Rating:  |
| 66.00 microhenries single component single winding and 90.00 microhenries single component single winding                           |
| Frequency Rating:   |
| 15.75 kilohertz single component  |
| Body Length:  |
| 0.625 inches  |
| Body Outside Diameter:  |
| 1.100 inches  |
| Maximum Operating Temp:   |
| 155.0 degrees celsius   |
| Winding Quantity:   |
| 1 single component  |
| Inclosure Type:   |
| Fully enclosed  |
| Mounting Facility Quantity:   |
| 1 single group  |
| Mounting Method:  |
| Threaded hole single group  |
| Rating Method:  |
| Electrical single component single winding and winding turns single component single winding  |
| Thread Size:  |
| 0.112 inches single group   |
| Winding Conductor Size:   |
| 0.05082 inches american wire gage single component single winding   |
| Winding Operating Current:  |
| 3.0 amperes dc single component single winding  |
| Dc Resistance Rating In Ohms:   |
| 0.020 single component single winding   |
| Test Data Document:   |
| 18876-13060916 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, |
| etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)                   |
| Thread Series Designator:   |
| Unc single group  |
| Terminal Type And Quantity:   |
| 2 wire lead   |
| Shelf Life:   |

N/a

## NSN 5950-01-188-6340

Reactor - Page 2 of 2



|  |  |  | ure: |  |
|--|--|--|------|--|
|  |  |  |      |  |
|  |  |  |      |  |

--

Demilitarization:

No

Fiig:

A058b0