

View Online at <https://aerobasegroup.com/nsn/5950-01-188-6361>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.678 inches single mounting facility single center group and 1.698 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.428 inches single mounting facility single center group and 1.448 inches single mounting facility single center group

Frequency Rating:

54.0 hertz single component and 66.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to core single component

Body Length:

Between 2.187 inches and 2.312 inches

Body Width:

Between 1.937 inches and 2.062 inches

Body Height:

Between 2.937 inches and 3.125 inches

Maximum Operating Temp:

155.0 degrees celsius

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thread Size:

0.138 inches single group

Winding Operating Voltage:

5.00 ac volts single component single secondary and 9.20 ac volts single component single secondary and 10.60 ac volts single component single secondary and 11.60 ac volts single component single secondary and 26.00 ac volts single component single secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

8 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0