

View Online at <https://aerobasegroup.com/nsn/5950-01-189-3194>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.250 inches 2nd mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.625 inches 2nd mounting facility single center group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Three phase to single phase single component

Maximum Transformer Power Rating:

50.0 volt-ampere single component

Body Length:

2.000 inches

Body Width:

2.000 inches

Body Height:

2.250 inches

Maximum Operating Temp:

130.0 degrees celsius

Distance Between Mounting Facility Centers:

1.250 inches 1st mounting facility single center group

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 2nd group

Mounting Method:

Threaded hole all groupings

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Thread Size:

0.138 inches all groupings

Winding Operating Current:

750.0 milliamperes ac single component 2nd secondary

Winding Power Rating:

4.7 volts-amperes single component 2nd secondary

Winding Operating Voltage:

6.30 ac volts single component 2nd secondary

Thread Series Designator:

Unc all groupings

Terminal Type And Quantity:

15 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0