

View Online at <https://aerobasegroup.com/nsn/5950-01-190-6779>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.000 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.438 inches single mounting facility single center group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Grounded to core and mounting single component

Body Length:

5.250 inches

Body Width:

3.595 inches

Body Height:

4.158 inches

Maximum Operating Temp:

65.0 degrees celsius

End Application:

Mk72m15 sdc; wsd: fire control system, missile mk 74 (fcs); virginia class cgn (41); kidd class ddg

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.190 inches single group

Winding Operating Current:

6.3 amperes ac single component 1st secondary

Criticality Code Justification:

Feat

Winding Operating Voltage:

2520.00 ac volts single component 2nd secondary

Special Features:

Weapon system essential

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

8 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0