## NSN 5950-01-190-7523

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-190-7523

Reliability Indicator:
Not established
Hazardous Locations/environmental Protection:
Moisture resistant
Center To Center Distance Between Mounting Facilities Parallel To Length:
2.500 inches all mounting facilities single center group
Center To Center Distance Between Mounting Facilities Parallel To Width:
2.500 inches all mounting facilities single center group
Frequency Rating:
400.0 hertz single component
Input-output Phase Relationship:
Single phase to single phase single component
Winding Shielding Method:
Internal shield brought out to terminal single component
Body Length:
Between 3.180 inches and 3.260 inches
Body Width:
Between 3.180 inches and 3.260 inches
Body Height:
Between 5.040 inches and 5.120 inches
Inclosure Type:
Fully enclosed
Mounting Facility Quantity:
4 all groupings
Mounting Method:
Threaded hole all groupings
Winding Function And Quantity:
1 primary single component and 1 secondary single component
Thread Size:
0.164 inches all groupings
Winding Operating Current:
370.0 milliamperes ac single component single primary
Winding Power Rating:
4.2 volts-amperes single component single primary
Winding Operating Voltage:
115.00 ac volts single component single primary
Thread Series Designator:
Unc all groupings
Terminal Type And Quantity:
2 threaded stud and 2 pin
Shelf Life:
N/a

## NSN 5950-01-190-7523

Power Transformer - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

Yes - demil/mli

Fiig:

A058b0

