

View Online at <https://aerobasegroup.com/nsn/5950-01-190-7523>

Reliability Indicator:

Not established

Hazardous Locations/environmental Protection:

Moisture resistant

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.500 inches all mounting facilities single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.500 inches all mounting facilities single center group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Length:

Between 3.180 inches and 3.260 inches

Body Width:

Between 3.180 inches and 3.260 inches

Body Height:

Between 5.040 inches and 5.120 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 all groupings

Mounting Method:

Threaded hole all groupings

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thread Size:

0.164 inches all groupings

Winding Operating Current:

370.0 milliamperes ac single component single primary

Winding Power Rating:

4.2 volts-amperes single component single primary

Winding Operating Voltage:

115.00 ac volts single component single primary

Thread Series Designator:

Unc all groupings

Terminal Type And Quantity:

2 threaded stud and 2 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A058b0