NSN 5950-01-192-0000

Power Transformer - Page 1 of 1



| view Online at https://aerobasegroup.com/nsn/5950-01-192-0000 |
|---|
| Reliability Indicator: |
| Not established |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 2.470 inches single mounting facility single center group and 2.530 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 1.940 inches single mounting facility single center group and 2.060 inches single mounting facility single center group |
| Mounting Slot Width: |
| 0.200 inches single group |
| Frequency Rating: |
| 50.0 hertz single component and 560.0 hertz single component |
| Input-output Phase Relationship: |
| Single phase to single phase single component |
| Body Length: |
| 3.600 inches |
| Body Width: |
| 3.200 inches |
| Body Height: |
| 3.400 inches |
| Maximum Operating Temp: |
| 115.0 degrees celsius |
| Inclosure Type: |
| Fully enclosed |
| Mounting Facility Quantity: |
| 4 single group |
| Mounting Method: |
| Slot single group |
| Winding Function And Quantity: |
| 1 primary single component and 2 secondary single component |
| Winding Operating Current: |
| 200.0 milliamperes ac single component all secondary |
| Winding Operating Voltage: |
| 12.80 ac volts single component all secondary |
| Terminal Type And Quantity: |
| 8 tab, solder lug |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| - - |
| Demilitarization: |
| No |

Fiig: A058b0