NSN 5950-01-192-1319

Current Transformer - Page 1 of 1



| View Online at https://aerobasegroup.com/nsn/5950-01-192-1319 |
|---|
| Reliability Indicator: |
| Not established |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 5.500 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 1.750 inches single mounting facility single center group |
| Mounting Hole Diameter: |
| 0.218 inches single group |
| Input-output Phase Relationship: |
| Three phase to three phase single component |
| Body Length: |
| 6.062 inches |
| End Application: |
| Landing craft air cushion (lcac). T-62 gas turbine systems. |
| Inclosure Type: |
| Fully enclosed |
| Mounting Facility Quantity: |
| 4 single group |
| Mounting Method: |
| Unthreaded hole single group |
| Winding Function And Quantity: |
| 1 primary single component and 1 secondary single component |
| Criticality Code Justification: |
| Feat |
| Winding Operating Voltage: |
| 30.00 ac volts single component single primary |
| Special Features: |
| Weapon system essential |
| Terminal Type And Quantity: |
| 6 connector, receptacle |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| |

Fiig:

A058b0