

View Online at <https://aerobasegroup.com/nsn/5950-01-192-3169>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.625 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.000 inches single mounting facility single center group

Frequency Rating:

50.0 hertz single component or 60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Maximum Transformer Power Rating:

300.0 volt-ampere single component

Winding Shielding Method:

Internal shield grounded to core single component

Body Length:

4.500 inches

Body Width:

3.938 inches

Body Height:

4.625 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Current:

2.6 amperes ac single component single secondary

Winding Operating Voltage:

220.00 ac volts single component single primary and 440.00 ac volts single component single primary

Terminal Type And Quantity:

1 cable w/connector and 1 connector, receptacle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0