## NSN 5950-01-192-3237

Reactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-192-3237

Reliability Indicator:
Not established
Turn Quantity:
128 single component 3rd winding
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.275 inches single mounting facility single center group
Center To Center Distance Between Mounting Facilities Parallel To Width:
1.025 inches single mounting facility single center group
Inductance Type:
Swinging
Inductance Rating:
375.00 microhenries single component 1st winding and 750.00 microhenries single component 1st winding
Frequency Rating:
80.0 kilohertz single component
Body Length:
1.600 inches
Body Width:
1.290 inches
Body Height:
1.310 inches
Maximum Operating Temp:
155.0 degrees celsius
Winding Quantity:
3 single component
Inclosure Type:
Fully enclosed
Mounting Facility Quantity:
4 single group
Mounting Method:
Threaded hole single group
Rating Method:
Electrical single component all winding and winding turns single component all winding
Features Provided:
Tinned wire leads
Thread Size:
0.112 inches single group
Winding Conductor Size:
0.03589 inches american wire gage single component 2nd winding
Winding Operating Current:
80.0 milliamperes dc single component 3rd winding and 1.2 amperes dc single component 3rd winding

**Dc Resistance Rating In Ohms:** 0.650 single component 3rd winding

## NSN 5950-01-192-3237

Reactor - Page 2 of 2



Thread Series Designator:
Unc single group
Terminal Type And Quantity:
6 wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A058b0