NSN 5950-01-192-5203

Power Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-01-192-5203

| Reliability Indicator: |
|--|
| Not established |
| Overall Length: |
| 4.500 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 3.750 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 3.000 inches single mounting facility single center group |
| Overall Width: |
| 3.750 inches |
| Mounting Hole Diameter: |
| 0.220 inches single group |
| Frequency Rating: |
| 60.0 hertz single component |
| Maximum Transformer Power Rating: |
| 250.0 watts single component |
| Inclosure Type: |
| Open |
| Mounting Facility Quantity: |
| 4 single group |
| Mounting Method: |
| Unthreaded hole single group |
| Winding Function And Quantity: |
| 2 primary single component and 4 secondary single component |
| Winding Operating Current: |
| 0.2 amperes ac single component all primary |
| Winding Operating Voltage: |
| 105.00 ac pounds per hour dry single component all primary and 210.00 ac pounds per hour with retaining chain single component all |
| primary or 117.00 ac pounds per hour dry single component all primary and 234.00 ac pounds per hour with retaining chain single |
| component all primary or 129.00 ac pounds per hour dry single component all primary and 258.00 ac pounds per hour with retaining chain |
| single component all primary |
| Terminal Type And Quantity: |
| 19 tab, solder lug |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A058h0 |