

View Online at <https://aerobasegroup.com/nsn/5950-01-192-8831>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.813 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.375 inches single mounting facility single center group

Mounting Slot Width:

0.203 inches single group

Frequency Rating:

50.0 hertz single component or 60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Maximum Transformer Power Rating:

100.0 volt-ampere single component

Body Length:

3.375 inches

Body Width:

3.375 inches

Body Height:

2.875 inches

Maximum Operating Temp:

105.0 degrees celsius

Inclosure Type:

Partially enclosed, double shell

Mounting Facility Quantity:

4 single group

Mounting Method:

Slot single group

Winding Function And Quantity:

2 primary single component and 1 secondary single component

Winding Operating Current:

869.0 milliamperes ac single component single secondary

Winding Operating Voltage:

220.00 ac volts single component all primary

Terminal Type And Quantity:

2 terminal block w/screws

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0