

View Online at <https://aerobasegroup.com/nsn/5950-01-192-9918>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

4.100 inches single mounting facili type 1st center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.750 inches single mounting facili type 1st center group

Mounting Hole Diameter:

0.307 inches all groupings and 0.318 inches all groupings

Frequency Rating:

50.0 hertz single component and 400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to core single component

Body Length:

4.800 inches

Body Width:

4.700 inches

Body Height:

4.000 inches

Distance Between Mounting Facility Centers:

4.100 inches single mounting facili type 2nd center group

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 1st group

Mounting Method:

Unthreaded hole all groupings

Winding Function And Quantity:

1 primary single component and 4 secondary single component

Winding Operating Current:

100.0 milliamperes dc single component 4th secondary

Winding Operating Voltage:

95.00 ac volts single component 1st secondary

Terminal Type And Quantity:

11 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0