

View Online at <https://aerobasegroup.com/nsn/5950-01-193-4924>

Reliability Indicator:

Not established

Hazardous Locations/environmental Protection:

Dust resistant and humidity resistant and salt spray resistant and fungus resistant and explosion resistant and rainproof

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Maximum Transformer Power Rating:

24.0 watts single component

Body Length:

1.470 inches

Body Width:

1.400 inches

Body Height:

1.280 inches

Maximum Operating Temp:

130.0 degrees celsius

Distance Between Mounting Facility Centers:

1.220 inches single mounting facility single center group

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

2 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thread Size:

0.112 inches single group

Winding Operating Current:

855.0 milliamperes ac single component single secondary

Winding Power Rating:

23.9 volts-amperes single component single secondary

Winding Operating Voltage:

28.00 ac volts single component single secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

5 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0