# NSN 5950-01-193-4924

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-193-4924

## Reliability Indicator:

Not established

### Hazardous Locations/environmental Protection:

Dust resistant and humidity resistant and salt spray resistant and fungus resistant and explosion resistant and rainproof

## Frequency Rating:

400.0 hertz single component

#### Input-output Phase Relationship:

Single phase to single phase single component

## Maximum Transformer Power Rating:

24.0 watts single component

#### Body Length:

1.470 inches

#### Body Width:

1.400 inches

# **Body Height:**

1.280 inches

## Maximum Operating Temp:

130.0 degrees celsius

# Distance Between Mounting Facility Centers:

1.220 inches single mounting facility single center group

# Inclosure Type:

Fully enclosed

# Mounting Facility Quantity:

2 single group

# Mounting Method:

Threaded hole single group

# Winding Function And Quantity:

1 primary single component and 1 secondary single component

#### Thread Size:

0.112 inches single group

# Winding Operating Current:

855.0 milliamperes ac single component single secondary

#### Winding Power Rating:

23.9 volts-amperes single component single secondary

#### Winding Operating Voltage:

28.00 ac volts single component single secondary

#### **Thread Series Designator:**

Unc single group

# Terminal Type And Quantity:

5 turret

#### Shelf Life:

N/a

# NSN 5950-01-193-4924

Power Transformer - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A058b0

