NSN 5950-01-193-5969

Current Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-01-193-5969

Reliability Indicator:
Not established
Overall Length:
4.812 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
3.500 inches single mounting facility single center group
Center To Center Distance Between Mounting Facilities Parallel To Width:
3.500 inches single mounting facility single center group
Overall Height:
5.438 inches
Overall Width:
2.000 inches
Mounting Hole Diameter:
0.438 inches single group
Frequency Rating:
50.0 hertz single component or 60.0 hertz single component
Input-output Phase Relationship:
Single phase to single phase single component
Inclosure Type:
Fully enclosed
Mounting Facility Quantity:
meaning a comp quantity.
2 single group
2 single group
2 single group Mounting Method:
2 single group Mounting Method: Unthreaded hole single group
2 single group Mounting Method: Unthreaded hole single group Winding Function And Quantity:
2 single group Mounting Method: Unthreaded hole single group Winding Function And Quantity: 1 primary single component
2 single group Mounting Method: Unthreaded hole single group Winding Function And Quantity: 1 primary single component Winding Operating Current:
2 single group Mounting Method: Unthreaded hole single group Winding Function And Quantity: 1 primary single component Winding Operating Current: 300.0 amperes ac single component single primary
2 single group Mounting Method: Unthreaded hole single group Winding Function And Quantity: 1 primary single component Winding Operating Current: 300.0 amperes ac single component single primary Special Features:
2 single group Mounting Method: Unthreaded hole single group Winding Function And Quantity: 1 primary single component Winding Operating Current: 300.0 amperes ac single component single primary Special Features: Primary rated but not included
2 single group Mounting Method: Unthreaded hole single group Winding Function And Quantity: 1 primary single component Winding Operating Current: 300.0 amperes ac single component single primary Special Features: Primary rated but not included Terminal Type And Quantity:
2 single group Mounting Method: Unthreaded hole single group Winding Function And Quantity: 1 primary single component Winding Operating Current: 300.0 amperes ac single component single primary Special Features: Primary rated but not included Terminal Type And Quantity: 2 threaded stud
2 single group Mounting Method: Unthreaded hole single group Winding Function And Quantity: 1 primary single component Winding Operating Current: 300.0 amperes ac single component single primary Special Features: Primary rated but not included Terminal Type And Quantity: 2 threaded stud Shelf Life:
2 single group Mounting Method: Unthreaded hole single group Winding Function And Quantity: 1 primary single component Winding Operating Current: 300.0 amperes ac single component single primary Special Features: Primary rated but not included Terminal Type And Quantity: 2 threaded stud Shelf Life: N/a
2 single group Mounting Method: Unthreaded hole single group Winding Function And Quantity: 1 primary single component Winding Operating Current: 300.0 amperes ac single component single primary Special Features: Primary rated but not included Terminal Type And Quantity: 2 threaded stud Shelf Life: N/a
2 single group Mounting Method: Unthreaded hole single group Winding Function And Quantity: 1 primary single component Winding Operating Current: 300.0 amperes ac single component single primary Special Features: Primary rated but not included Terminal Type And Quantity: 2 threaded stud Shelf Life: N/a Unit Of Measure:
2 single group Mounting Method: Unthreaded hole single group Winding Function And Quantity: 1 primary single component Winding Operating Current: 300.0 amperes ac single component single primary Special Features: Primary rated but not included Terminal Type And Quantity: 2 threaded stud Shelf Life: N/a Unit Of Measure: Demilitarization: