## NSN 5950-01-194-7373

Reactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-194-7373

| Reliability Indicator:                                                    |
|---------------------------------------------------------------------------|
| Not established                                                           |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 0.810 inches single mounting facility single center group                 |
| Center To Center Distance Between Mounting Facilities Parallel To Width:  |
| 0.375 inches single mounting facility single center group                 |
| Overall Height:                                                           |
| 1.130 inches                                                              |
| Inductance Type:                                                          |
| Fixed                                                                     |
| Inductance Rating:                                                        |
| 2.00 millihenries single component single winding                         |
| Frequency Rating:                                                         |
| 40.0 kilohertz single component                                           |
| Body Length:                                                              |
| 1.130 inches                                                              |
| Body Width:                                                               |
| 0.750 inches                                                              |
| Body Height:                                                              |
| 0.880 inches                                                              |
| Winding Quantity:                                                         |
| 1 single component                                                        |
| Inclosure Type:                                                           |
| Fully enclosed                                                            |
| Mounting Facility Quantity:                                               |
| 2 single group                                                            |
| Mounting Method:                                                          |
| Threaded hole single group                                                |
| Rating Method:                                                            |
| Electrical single component single winding                                |
| Thread Size:                                                              |
| 0.112 inches single group                                                 |
| Winding Operating Current:                                                |
| 1.0 amperes dc single component single winding                            |
| Dc Resistance Rating In Ohms:                                             |
| 0.500 single component single winding                                     |
| Thread Series Designator:                                                 |
| Unc single group                                                          |
| Terminal Type And Quantity:                                               |
| 2 turret                                                                  |
| Shalf Life:                                                               |

N/a

## NSN 5950-01-194-7373

Reactor - Page 2 of 2



|   | 1  | :. | ~  | 84  |    |    |      |   |
|---|----|----|----|-----|----|----|------|---|
| ι | JN | IT | UΤ | IVI | ea | Sι | ire: | • |

--

Demilitarization:

No

Fiig:

A058b0