## NSN 5950-01-195-1967

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-195-1967

## **Reliability Indicator:**

Not established

#### Center To Center Distance Between Mounting Facilities Parallel To Length:

0.750 inches single mounting facility single center group

#### **Center To Center Distance Between Mounting Facilities Parallel To Width:**

0.660 inches single mounting facility single center group

#### Frequency Rating:

400.0 hertz single component

#### Input-output Phase Relationship:

Single phase to single phase single component

#### **Maximum Transformer Power Rating:**

5.2 volt-ampere single component

#### **Body Length:**

1.100 inches

### **Body Width:**

0.980 inches

#### **Body Height:**

1.000 inches

## **Inclosure Type:**

Fully enclosed

## **Mounting Facility Quantity:**

2 single group

#### **Mounting Method:**

Threaded hole single group

## **Winding Function And Quantity:**

1 primary single component and 1 secondary single component

## Thread Size:

0.112 inches single group

#### **Winding Operating Current:**

200.0 milliamperes ac single component single secondary

## **Winding Power Rating:**

5.3 volts-amperes single component single secondary

## **Criticality Code Justification:**

Feat

## **Winding Operating Voltage:**

25.94 ac volts single component single secondary and 26.46 ac volts single component single secondary

## **Special Features:**

Weapons system essential

## **Thread Series Designator:**

Unc single group

## **Terminal Type And Quantity:**

4 turret

# NSN 5950-01-195-1967

Power Transformer - Page 2 of 2



She	lf	Life:	
Oile	••	LIIV.	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A058b0