

View Online at <https://aerobasegroup.com/nsn/5950-01-195-1967>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.750 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.660 inches single mounting facility single center group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Maximum Transformer Power Rating:

5.2 volt-ampere single component

Body Length:

1.100 inches

Body Width:

0.980 inches

Body Height:

1.000 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

2 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thread Size:

0.112 inches single group

Winding Operating Current:

200.0 milliamperes ac single component single secondary

Winding Power Rating:

5.3 volts-amperes single component single secondary

Criticality Code Justification:

Feat

Winding Operating Voltage:

25.94 ac volts single component single secondary and 26.46 ac volts single component single secondary

Special Features:

Weapons system essential

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

4 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0