

View Online at <https://aerobasegroup.com/nsn/5950-01-198-7922>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.750 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

4.062 inches single mounting facility single center group

Mounting Slot Width:

0.219 inches single group

Frequency Rating:

50.0 hertz single component or 60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Maximum Transformer Power Rating:

350.0 volt-ampere single component

Winding Shielding Method:

Internally shielded single component

Body Length:

6.688 inches

Body Width:

4.938 inches

Body Height:

4.250 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Bracket single group and slot single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Current:

3.045 amperes ac single component single secondary

Winding Operating Voltage:

208.00 ac volts single component single primary and 460.00 ac volts single component single primary

Terminal Type And Quantity:

6 standoff, screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0