

View Online at <https://aerobasegroup.com/nsn/5950-01-199-4297>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.125 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.250 inches single mounting facility single center group

Mounting Slot Width:

0.203 inches single group

Frequency Rating:

47.0 hertz single component and 66.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Length:

4.066 inches

Body Width:

3.125 inches

Body Height:

3.375 inches

Maximum Operating Temp:

90.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Slot single group

Winding Function And Quantity:

2 primary single component and 2 secondary single component

Winding Operating Current:

4.0 amperes ac single component 1st secondary

Winding Operating Voltage:

95.00 ac volts single component all primary and 125.00 ac volts single component all primary and 200.00 ac volts single component all primary and 240.00 ac volts single component all primary

Terminal Type And Quantity:

11 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0