

View Online at <https://aerobasegroup.com/nsn/5950-01-199-7225>

Reliability Indicator:

Not established

Overall Length:

Between 3.409 inches and 3.471 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.484 inches single mounting facility single center group and 2.516 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.234 inches single mounting facility single center group and 2.266 inches single mounting facility single center group

Overall Height:

Between 4.812 inches and 4.938 inches

Overall Width:

Between 2.849 inches and 2.911 inches

Frequency Rating:

50.0 hertz single component or 60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Maximum Transformer Power Rating:

120.0 volt-ampere single component

Maximum Operating Temp:

130.0 degrees celsius

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thread Size:

0.190 inches single group

Winding Operating Current:

1.09 amperes ac single component single secondary

Winding Operating Voltage:

115.00 ac volts single component single primary

Test Data Document:

81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unf single group

Terminal Type And Quantity:

5 wire hook

Specification Data:

81349-mil-t-27/319 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0