## NSN 5950-01-199-9077

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-199-9077

## **Reliability Indicator:**

Not established

#### **Center To Center Distance Between Mounting Facilities Parallel To Length:**

3.720 inches single mounting facility single center group and 3.780 inches single mounting facility single center group

#### **Center To Center Distance Between Mounting Facilities Parallel To Width:**

3.160 inches single mounting facility single center group and 3.340 inches single mounting facility single center group

#### **Frequency Rating:**

60.0 hertz single component

#### Input-output Phase Relationship:

Single phase to single phase single component

#### Winding Shielding Method:

Internal shield grounded to core single component

#### **Body Length:**

4.690 inches

#### **Body Width:**

4.000 inches

#### **Body Height:**

4.000 inches

## **Maximum Operating Temp:**

130.0 degrees celsius

## Inclosure Type:

Fully enclosed

#### **Mounting Facility Quantity:**

4 single group

## **Mounting Method:**

Threaded hole single group

## **Winding Function And Quantity:**

1 primary single component and 7 secondary single component

#### **Thread Size:**

0.190 inches single group

## **Winding Operating Current:**

9.0 amperes ac single component 1st secondary

## **Winding Power Rating:**

4.9 volts-amperes single component 4th secondary

## Winding Operating Voltage:

19.00 ac volts single component 1st secondary

#### **Special Features:**

One primary winding and seven secondary windings

## **Thread Series Designator:**

Unf single group

#### **Terminal Type And Quantity:**

17 eyelet and 3 wire hook

# NSN 5950-01-199-9077

Power Transformer - Page 2 of 2



				-
C I	20	lŧ.	l i	fe:
J.	16		_,	ıc.

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A058b0