NSN 5950-01-201-3750

Radio Frequency Coil - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-201-3750

| Delichility Indicatory |
|---|
| Reliability Indicator: |
| Not established |
| Turn Quantity: |
| 11-1/2 single component single winding |
| Inductance Rating: |
| 1.98 microhenries single component single winding and 2.42 microhenries single component single winding |
| Coil Form Type: |
| Hollow single component |
| Core Construction: |
| Solid single component |
| Adjustment Device Drive Type: |
| Hex socket single component |
| Body Length: |
| 0.486 inches |
| Body Outside Diameter: |
| 0.375 inches |
| Maximum Operating Temp: |
| 105.0 degrees celsius |
| Inclosure Type: |
| Fully enclosed |
| Mounting Method: |
| Terminal single group |
| Rating Method: |
| Electrical single component single winding and winding turns single component single winding |
| Winding Conductor Size: |
| 0.00631 inches american wire gage single component single winding |
| Winding Operating Current: |
| 157.0 milliamperes dc single component single winding |
| Dc Resistance Rating In Ohms: |
| 0.120 single component single winding |
| Quality Factor: |
| 80 single component single winding and 85 single component single winding |
| Adjustment Method And Quantity: |
| 1 adjustable core single component |
| Terminal Type And Quantity: |
| 2 pin |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

No

NSN 5950-01-201-3750

Radio Frequency Coil - Page 2 of 2



Fiig:

A058b0