

View Online at <https://aerobasegroup.com/nsn/5950-01-201-4457>

**Reliability Indicator:**

Not established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

2.615 inches single mounting facility single center group and 2.635 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

2.115 inches single mounting facility single center group and 2.135 inches single mounting facility single center group

**Frequency Rating:**

57.0 hertz single component and 63.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single component

**Winding Shielding Method:**

Internal shield brought out to terminal single component

**Body Length:**

Between 3.530 inches and 3.590 inches

**Body Width:**

Between 3.030 inches and 3.090 inches

**Body Height:**

Between 4.850 inches and 4.910 inches

**Maximum Operating Temp:**

105.0 degrees celsius

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Threaded stud single group

**Winding Function And Quantity:**

1 primary single component and 3 secondary single component

**Thread Size:**

0.164 inches single group

**Winding Operating Current:**

1.1 amperes ac single component all secondary

**Winding Power Rating:**

36.9 volts-amperes single component 2nd secondary

**Winding Operating Voltage:**

33.50 ac volts single component 2nd secondary

**Test Data Document:**

03024-8-60014627 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Thread Series Designator:**

Unc single group

**Terminal Type And Quantity:**

14 turret

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0