NSN 5950-01-201-5288

Reactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-201-5288

Reliability Indicator:
Not established
Hazardous Locations/environmental Protection:
Flame resistant and fungus proof and vibration resistant
Mounting Slot Width:
0.140 inches single group
Inductance Type:
Swinging
Inductance Rating:
15.00 millihenries single component single winding and 30.00 millihenries single component single winding
Frequency Rating:
400.0 hertz single component
Body Length:
1.750 inches
Body Width:
1.190 inches
Body Height:
0.820 inches
Maximum Operating Temp:
100.0 degrees celsius
Distance Between Mounting Facility Centers:
1.437 inches single mounting facility single center group
Winding Quantity:
1 single component
Inclosure Type:
Fully enclosed
Mounting Facility Quantity:
2 single group
Mounting Method:
Slot single group
Rating Method:
Electrical single component single winding
Winding Operating Current:
0.0 amperes dc single component single winding and 1.0 amperes dc single component single winding
Dc Resistance Rating In Ohms:
3.100 single component single winding
Terminal Type And Quantity:
2 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:

NSN 5950-01-201-5288

Reactor - Page 2 of 2



Demilitarization:

No

Fiig:

A058b0