## NSN 5950-01-203-1133

Pulse Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-203-1133

### **Reliability Indicator:**

Not established

### Center To Center Distance Between Mounting Facilities Parallel To Length:

2.750 inches single mounting facility single center group

### **Center To Center Distance Between Mounting Facilities Parallel To Width:**

2.125 inches single mounting facility single center group

### **Overall Height:**

3.750 inches

### **Inductance Rating:**

2.15 millihenries single component single primary

### Frequency Rating:

400.0 hertz single component

### **Primary To Secondary Turn Ratio:**

1 to 1 single component

### **Pulse Repetition Rate:**

1.2 kilohertz single component

### **Winding Shielding Method:**

Internal shield grounded to core single component

### **Body Length:**

3.750 inches

### **Body Width:**

3.000 inches

### **Body Height:**

3.250 inches

### **Maximum Operating Temp:**

130.0 degrees celsius

### Inclosure Type:

Fully enclosed

### **Mounting Facility Quantity:**

4 single group

### **Mounting Method:**

Threaded stud single group

### **Winding Function And Quantity:**

1 primary single component and 1 secondary single component

### **Thread Size:**

0.190 inches single group

### **Winding Operating Current:**

2.5 amperes dc single component single secondary

### Dc Resistance Rating In Ohms:

0.300 single component single secondary

### **Thread Series Designator:**

Unf single group

# NSN 5950-01-203-1133

Pulse Transformer - Page 2 of 2



Terminal Type And Quantity:
4 turret
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A058b0