NSN 5950-01-203-1140

Reactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-203-1140

View Online at https://aerobasegroup.com/nsn/5950-01-203-1140
Reliability Indicator:
Not established
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.925 inches single mounting facility single center group and 0.935 inches single mounting facility single center group
Center To Center Distance Between Mounting Facilities Parallel To Width:
0.925 inches single mounting facility single center group and 0.935 inches single mounting facility single center group
Mounting Hole Diameter:
0.166 inches single group
Inductance Type:
Swinging
Inductance Rating:
220.00 microhenries single component single winding and 293.00 microhenries single component single winding
Frequency Rating:
360.0 hertz single component and 30.0 kilohertz single component
Body Length:
1.280 inches
Body Width:
1.280 inches
Body Height:
Between 0.690 inches and 0.750 inches
Maximum Operating Temp:
65.0 degrees celsius
Winding Quantity:
1 single component
Inclosure Type:
Fully enclosed
Mounting Facility Quantity:
4 single group
Mounting Method:
Unthreaded hole single group
Rating Method:
Electrical single component single winding
Winding Operating Current:
3.0 amperes ac single component single winding and 3.5 amperes ac single component single winding
Dc Resistance Rating In Ohms:
0.065 single component single winding
Terminal Type And Quantity:
2 wire hook
Shelf Life:
N/a

--

Unit Of Measure:

NSN 5950-01-203-1140

Reactor - Page 2 of 2



_		••	• •				
וו	em	ш	112	rız	211	n	٠.

No

Fiig:

A058b0