

View Online at <https://aerobasegroup.com/nsn/5950-01-203-3293>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.812 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.750 inches single mounting facility single center group

Mounting Slot Width:

0.218 inches single group

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Three phase to three phase single component

Transformer Winding Connection Type:

Delta-delta

Maximum Transformer Power Rating:

7.0 watts single component

Winding Shielding Method:

Primary and secondary shielded and brought out to terminal single component

Body Length:

4.250 inches

Body Width:

2.410 inches

Body Height:

3.630 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Bracket single group and slot single group

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Winding Operating Current:

3.25 amperes ac single component 1st secondary

Winding Operating Voltage:

8.00 ac pounds per hour wet single component 2nd secondary

Terminal Type And Quantity:

1 terminal block w/screws

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0