## NSN 5950-01-206-3739

Reactor - Page 1 of 2

**Reliability Indicator:** 

Not established



View Online at https://aerobasegroup.com/nsn/5950-01-206-3739

**Center To Center Distance Between Mounting Facilities Parallel To Length:** 

| 1.620 inches single mounting facility single center group                |
|--|
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 0.813 inches single mounting facility single center group                |
| Inductance Type:   |
| Fixed  |
| Inductance Rating:   |
| 25.00 microhenries single component single winding                       |
| Frequency Rating:  |
| 40.0 kilohertz single component  |
| Body Length:   |
| 2.000 inches   |
| Body Width:  |
| 1.250 inches   |
| Body Height:   |
| 1.400 inches   |
| Winding Quantity:  |
| 1 single component   |
| Inclosure Type:  |
| Fully enclosed   |
| Mounting Facility Quantity:  |
| 4 single group   |
| Mounting Method:   |
| Threaded hole single group   |
| Rating Method:   |
| Electrical single component single winding                               |
| Thread Size:   |
| 0.138 inches single group  |
| Winding Operating Current:   |
| 50.0 amperes dc single component single winding                          |
| Dc Resistance Rating In Ohms:  |
| 0.004 single component single winding                                    |
| Thread Series Designator:  |
| Unc single group   |
| Terminal Type And Quantity:  |
| 2 wire lead  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |

## NSN 5950-01-206-3739

Reactor - Page 2 of 2



Demilitarization:

No

Fiig:

A058b0