## NSN 5950-01-207-3496

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-207-3496

## **Reliability Indicator:**

Not established

#### **Center To Center Distance Between Mounting Facilities Parallel To Length:**

2.180 inches and 2.200 inches single mounting facility single center group

#### Center To Center Distance Between Mounting Facilities Parallel To Width:

1.740 inches and 1.760 inches single mounting facility single center group

#### Frequency Rating:

50.0 hertz and 400.0 hertz single component

#### Input-output Phase Relationship:

Single phase to single phase single component

#### Winding Shielding Method:

Internal shield brought out to terminal single component

#### **Body Length:**

Between 2.590 inches and 2.610 inches

#### **Body Width:**

Between 2.190 inches and 2.210 inches

#### **Body Height:**

2.500 inches

## Inclosure Type:

Fully enclosed

## **Mounting Facility Quantity:**

4 single group

#### **Mounting Method:**

Unthreaded hole single group

#### **Winding Function And Quantity:**

2 primary and 2 secondary single component

## **Features Provided:**

Color coded lead

#### Cubic Measure (non-core):

14.4 cubic inches

#### **Winding Operating Current:**

1.0 amperes dc single component 1st secondary

### **Winding Operating Voltage:**

9.00 dc volts single component 1st secondary

#### **Terminal Type And Quantity:**

9 wire lead

#### Shelf Life:

N/a

## **Unit Of Measure:**

--

#### **Demilitarization:**

No

# NSN 5950-01-207-3496

Power Transformer - Page 2 of 2



Fiig:

A058b0