## NSN 5950-01-208-3523

Power Transformer - Page 1 of 2

Reliability Indicator:

Not established

No



View Online at https://aerobasegroup.com/nsn/5950-01-208-3523

| Center To Center Distance Between Mounting Facilities Parallel To Length: |
|---|
| 3.440 inches single mounting facility single center group                 |
| Center To Center Distance Between Mounting Facilities Parallel To Width:  |
| 2.750 inches single mounting facility single center group                 |
| Mounting Hole Diameter:   |
| 0.218 inches single group   |
| Frequency Rating:   |
| 60.0 hertz single component   |
| Input-output Phase Relationship:  |
| Single phase to single phase single component                             |
| Winding Shielding Method:   |
| Core grounded and brought out to terminal single component                |
| Body Length:  |
| 4.120 inches  |
| Body Width:   |
| 3.440 inches  |
| Body Height:  |
| 2.750 inches  |
| Inclosure Type:   |
| Fully enclosed  |
| Mounting Facility Quantity:   |
| 4 single group  |
| Mounting Method:  |
| Unthreaded hole single group  |
| Winding Function And Quantity:  |
| 1 primary and 4 secondary single component                                |
| Cubic Measure (non-core):   |
| 38.9 cubic inches   |
| Winding Operating Current:  |
| 55.0 milliamperes ac single component single primary                      |
| Winding Operating Voltage:  |
| 28.30 ac volts single component 1st secondary                             |
| Terminal Type And Quantity:   |
| 8 tab, solder lug and 3 wire lead   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |

## NSN 5950-01-208-3523

Power Transformer - Page 2 of 2



Fiig:

A058b0