## NSN 5950-01-208-4783

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-208-4783

Reliability Indicator:
Not established
Overall Length:
2.080 inches
Overall Height:
1.250 inches
Overall Width:
Between 1.480 inches and 1.560 inches
Mounting Hole Diameter:
0.140 inches single group
Frequency Rating:
380.0 hertz single component and 420.0 hertz single component
Input-output Phase Relationship:
Single phase to single phase single component
Winding Shielding Method:
Internal shield brought out to terminal single component
Maximum Operating Temp:
170.0 degrees celsius
Distance Between Mounting Facility Centers:
1.740 inches single mounting facility single center group and 1.760 inches single mounting facility single center group
Inclosure Type:
Fully enclosed
Mounting Facility Quantity:
2 single group
Mounting Method:
Unthreaded hole single group
Winding Function And Quantity:
1 primary single component and 3 secondary single component
Winding Operating Current:
48.0 milliamperes ac single component all secondary
Winding Power Rating:
5.52 volts-amperes single component all secondary
Criticality Code Justification:
Feat
Winding Operating Voltage:
353.00 ac volts single component single primary and 430.00 ac volts single component single primary
Special Features:
openial realares.
Nuclear hardness critical item
Nuclear hardness critical item

N/a

## NSN 5950-01-208-4783

Power Transformer - Page 2 of 2



		• •			
ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A058b0