

View Online at <https://aerobasegroup.com/nsn/5950-01-209-0604>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.250 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.000 inches single mounting facility single center group

Mounting Slot Width:

0.188 inches single group

Frequency Rating:

50.0 hertz or 60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Inclosure grounded single component

Body Length:

5.250 inches

Body Width:

3.875 inches

Body Height:

4.625 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Slot single group

Winding Function And Quantity:

1 primary and 2 secondary single component

Winding Operating Current:

3.0 amperes ac single component single primary

Winding Power Rating:

350.0 volts-amperes single component single primary

Winding Operating Voltage:

115.00 ac volts single component single primary

Unpackaged Unit Weight (non-core):

14.000 pounds

Terminal Type And Quantity:

8 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0