## NSN 5950-01-210-0110

Reactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-210-0110

view example at this polytaclobacog to approximate to the example at the example
Reliability Indicator:
Not established
Turn Quantity:
23-1/2 single component single winding
Mounting Hole Diameter:
0.124 inches single group and 0.130 inches single group
Inductance Type:
Fixed
Inductance Rating:
39.00 microhenries single component single winding
Frequency Rating:
40.0 kilohertz single component
Body Length:
Between 1.055 inches and 1.075 inches
Body Outside Diameter:
Between 0.802 inches and 0.822 inches
Maximum Operating Temp:
130.0 degrees celsius
Winding Quantity:
1 single component
Inclosure Type:
Fully enclosed
Mounting Facility Quantity:
1 single group
Mounting Method:
Unthreaded hole single group
Rating Method:
Electrical single component single winding and winding turns single component single winding
Winding Conductor Size:
0.04030 inches american wire gage single component single winding
Winding Operating Current:
4.9 amperes dc single component single winding
Dc Resistance Rating In Ohms:
0.026 single component single winding
Terminal Type And Quantity:
2 wire lead
Specification Data:
86360-181c2030-05 manufacturers source control
Shelf Life:
N/a
Unit Of Measure:

## NSN 5950-01-210-0110

Reactor - Page 2 of 2



em			

No

Fiig:

A058b0