NSN 5950-01-210-9880

Reactor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-01-210-9880

Reliability Indicator:
Not established
Mounting Hole Diameter:
0.188 inches single group
Inductance Type:
Fixed
Inductance Rating:
3.00 henry single component single winding
Body Length:
2.375 inches
Body Width:
1.188 inches
Body Height:
1.438 inches
Distance Between Mounting Facility Centers:
2.000 inches single mounting facility single center group
Winding Quantity:
1 single component
Inclosure Type:
Open
Mounting Facility Quantity:
2 single group
2 single group Mounting Method:
Mounting Method:
Mounting Method: Unthreaded hole single group
Mounting Method: Unthreaded hole single group Rating Method:
Mounting Method: Unthreaded hole single group Rating Method: Electrical single component single winding
Mounting Method: Unthreaded hole single group Rating Method: Electrical single component single winding Winding Operating Current:
Mounting Method: Unthreaded hole single group Rating Method: Electrical single component single winding Winding Operating Current: 75.0 milliamperes dc single component single winding
Mounting Method: Unthreaded hole single group Rating Method: Electrical single component single winding Winding Operating Current: 75.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms:
Mounting Method: Unthreaded hole single group Rating Method: Electrical single component single winding Winding Operating Current: 75.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 200.000 single component single winding
Mounting Method: Unthreaded hole single group Rating Method: Electrical single component single winding Winding Operating Current: 75.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 200.000 single component single winding Terminal Type And Quantity:
Mounting Method: Unthreaded hole single group Rating Method: Electrical single component single winding Winding Operating Current: 75.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 200.000 single component single winding Terminal Type And Quantity: 2 wire lead
Mounting Method: Unthreaded hole single group Rating Method: Electrical single component single winding Winding Operating Current: 75.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 200.000 single component single winding Terminal Type And Quantity: 2 wire lead Shelf Life:
Mounting Method: Unthreaded hole single group Rating Method: Electrical single component single winding Winding Operating Current: 75.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 200.000 single component single winding Terminal Type And Quantity: 2 wire lead Shelf Life: N/a
Mounting Method: Unthreaded hole single group Rating Method: Electrical single component single winding Winding Operating Current: 75.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 200.000 single component single winding Terminal Type And Quantity: 2 wire lead Shelf Life: N/a
Mounting Method: Unthreaded hole single group Rating Method: Electrical single component single winding Winding Operating Current: 75.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 200.000 single component single winding Terminal Type And Quantity: 2 wire lead Shelf Life: N/a Unit Of Measure:
Mounting Method: Unthreaded hole single group Rating Method: Electrical single component single winding Winding Operating Current: 75.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 200.000 single component single winding Terminal Type And Quantity: 2 wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: