## NSN 5950-01-211-4482

Reactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-211-4482

Reliability	Indicator:
-------------	------------

Not established

#### **Hazardous Locations/environmental Protection:**

Moisture resistant and vibration resistant

**Overall Length:** 

1.440 inches

#### Center To Center Distance Between Mounting Facilities Parallel To Length:

1.380 inches single mounting facility single center group

#### **Center To Center Distance Between Mounting Facilities Parallel To Width:**

1.120 inches single mounting facility single center group

**Overall Height:** 

1.878 inches

**Overall Width:** 

1.380 inches

**Inductance Type:** 

Fixed

**Inductance Rating:** 

15.00 millihenries single component single winding

Frequency Rating:

2.4 kilohertz single component

#### **Maximum Operating Temp:**

155.0 degrees celsius

Winding Quantity:

1 single component

**Inclosure Type:** 

Fully enclosed

#### **Mounting Facility Quantity:**

2 single group

**Mounting Method:** 

Threaded hole single group

**Rating Method:** 

Electrical single component single winding

Thread Size:

0.112 inches single group

#### **Winding Operating Current:**

1.8 amperes dc single component single winding

### Dc Resistance Rating In Ohms:

1.200 single component single winding

**Thread Series Designator:** 

Unc single group

#### **Terminal Type And Quantity:**

2 turret

# NSN 5950-01-211-4482

Reactor - Page 2 of 2



_					
٠.	n	_	I+	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A058b0