

View Online at <https://aerobasegroup.com/nsn/5950-01-211-9392>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.000 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.375 inches single mounting facility single center group

Mounting Hole Diameter:

0.170 inches and 0.176 inches single group

Frequency Rating:

20.0 kilohertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Length:

Between 2.310 inches and 2.330 inches

Body Width:

1.700 inches

Body Height:

1.822 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Unthreaded hole single group

Winding Function And Quantity:

1 primary and 1 secondary single component

Cubic Measure (non-core):

7.2 cubic inches

Winding Operating Current:

60.0 amperes ac single component single secondary

Winding Operating Voltage:

231.00 ac volts single component single primary

Unpackaged Unit Weight (non-core):

110.000 pounds

Terminal Type And Quantity:

4 turret and 3 ribbon

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0