## NSN 5950-01-212-0233

Reactor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-01-212-0233

| Reliability Indicator:   |
|--|
| Not established  |
| Turn Quantity:   |
| 132 single component single winding  |
| Inductance Rating:   |
| 3.00 millihenries single component single winding  |
| Frequency Rating:  |
| 10.0 kilohertz single component  |
| Body Length:   |
| 0.740 inches   |
| Body Outside Diameter:   |
| 1.120 inches   |
| Winding Quantity:  |
| 1 single component   |
| Inclosure Type:  |
| Fully enclosed   |
| Mounting Method:   |
| Threaded bushing single group  |
| Rating Method:   |
| Electrical single component single winding and winding turns single component single winding |
| Features Provided:   |
| Color coded lead   |
| Winding Conductor Size:  |
| 0.01790 inches american wire gage single component single winding                            |
| Winding Operating Current:   |
| 1.0 amperes dc single component single winding   |
| Dc Resistance Rating In Ohms:  |
| 0.900 single component single winding  |
| Terminal Type And Quantity:  |
| 2 wire lead  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| No   |
| Fiig:  |
| A058b0   |
|  |