## NSN 5950-01-212-5764

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-212-5764

| Thread Class (non-core):  |
|---|
| Unable to decode  |
| Thread Direction (non-core):  |
| Unable to decode  |
| Reliability Indicator:  |
| Not established   |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 1.250 inches single mounting facility single center group                 |
| Center To Center Distance Between Mounting Facilities Parallel To Width:  |
| 1.000 inches single mounting facility single center group                 |
| Frequency Rating:   |
| 400.0 hertz single component  |
| Input-output Phase Relationship:  |
| Single phase to single phase single component                             |
| Body Length:  |
| 1.500 inches  |
| Body Width:   |
| 1.250 inches  |
| Body Height:  |
| 1.250 inches  |
| Inclosure Type:   |
| Fully enclosed  |
| Mounting Facility Quantity:   |
| 4 single group  |
| Mounting Method:  |
| Threaded stud single group  |
| Winding Function And Quantity:  |
| 1 primary and 2 secondary single component                                |
| Thread Size:  |
| 0.138 inches single group   |
| Winding Operating Current:  |
| 5.0 amperes ac single component 1st secondary                             |
| Winding Operating Voltage:  |
| 6.00 ac volts single component 1st secondary                              |
| Thread Series Designator:   |
| Unc single group  |
| Terminal Type And Quantity:   |
| 6 wire hook   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |

--

## NSN 5950-01-212-5764

Power Transformer - Page 2 of 2



Demilitarization:

No

Fiig:

A058b0